

MINI DISPLAY



Developed in response to many enquiries, A+T has developed the MINI display for race yacht and superyacht applications. Typically this would be for a single parameter such as load or string-pot position and mounted close to the related winch or control buttons.

B&G has a current product (10/10) for this, but the comment is that it is too bulky for some applications. Its size is $114 \times 66 \times 51$ mm, weight 225 gm. Digits are 20 mm high.

A+T MINI display is shown below with dimensions 92 x 58 x 22mm, weight 98gm. Digits are 18mm high



B&G 10/10

To relative scale

A+T MINI

Main Features

- Thickness and weight are minimised.
- Fully sealed units, Bonded LCD and no possibility for water ingress so can be mounted in the wettest areas..
- Single item of data displayed.
- Two options of driving:-
 - Connect to an A+T MFD (up to 4 MINIs can be driven from one MFD) where the data item can be selected
 - Connect directly to a DLA1 loadcell amplifier (which also will take a linear input)
- Backlighting is provided colours red or green user selectable.
- OEM custom version available for system builders to drive directly

A+T Instruments Ltd. 235 Bentley Way, Lymington, SO41 8JW, UK +44 (0)1590 718182

<u>info@AandTinstruments.com</u> www.AandTinstruments.com



MINI DISPLAY

Typical configurations







Fastnet for B&G H2000 and H3000 systems and displays

•

4



With A+T MFD for display set-up & lighting control



With A+T DLA1 Loadcell amplifier (also analogue input)

Warranty and support

- 2 years warranty is offered on A+T products on return to factory basis
- Warranty starts from earliest date first used or 1 year after leaving factory
- 24/7 telephone support is provided direct from A+T Instruments Ltd

A+T Instruments Ltd.

235 Bentley Way, Lymington, SO41 8JW, UK +44 (0)1590 718182